

For the Finest in Residential, Farm and Commercial Buildings



42x64x12



30x40x10



60x104x18



30x56x9



48x48x10



36x60x10



Colors in this brochure are for illustration purposes and may vary from actual color and finish.





30x48x10



40x64x12



30x40x10



42x64x14



48x80x12



24X48X10 and 24X24X8



30x56x14

R.C. Buildings Standard Clear Span Widths:
24-27-30-32-36-42-45-48-51-54-60-66-72-80
Truss and Post Spacing Standard 8' oc.
Various Heights Available 8' thru 20'




32x40x10



24x32x12



30X40X10



Post Anchor

16" Diameter Holes
 4' Deep from Level Grade
 80#'s of 5,000# Concrete Mix for Pad.
 80#'s of 5,000# Concrete Mix for Anchor.
 Total of 160#'s used. Buildings wider than 60' have an additional 80#'s added.

6x6 Treated Post Grade #2 and Better

Yellow Pine 6x6 Posts are Kiln Dried before Treating, this allows Treatment to follow the Grain of Wood from Ends of Post for 100% Penetration of Sapwood. Minimum of .60 CCA Pressure Treatment. No Splices. 6x6's have 5 1/2 more square inches of wood than 3-2x6's, that is 22% more.



#1 Yellow Pine

All #1 Yellow Pine Lumber used throughout building. Stronger, holds fasteners better.

Corner Braces #1 YP

Standard at each corner.

2x4 Wall Girts #1 YP

Wall Girts 24" Spacing

2x4 Strip Sheathing #1 YP

2x4 Strip Sheathing on top of trusses. 24" Spacing. Lapped one foot at splices.

2x6 Eave Boards #1 YP

Post Notch

6x6 Posts are notched for direct support of Truss. Truss is nailed and Bolted.

Knee Brace #1 YP

Double 2x4 Knee Braces are used for additional strength.

Trusses

D.S.S. and M.S.R. Lumber. Straight Bottom Chord is Standard. Allows full clearance throughout building. Minimum 25# per sq ft Roof Load. Standard Truss Spacing 8' oc.

End Wall Post

End wall posts go to top of end wall for additional strength.

Optional Concrete Foundation

Concrete foundation with 4X6 Treated Plate and U-Post Brackets.



Optional Plasti-Sleeve Post Protectors

A one piece molded plastic sleeve with an enclosed bottom designed to fit post cleanly. Made from a high quality HDPE plastic which has an in-ground decay resistance of hundred's of years. Protects against post rot, decay or insect attack. Length 5' 6"



2-Piece Sliding Door Center

Center Door Guide on a 6x6 post buried in the center of the door opening with concrete. All components are made of heavy steel. 2-piece Door Centers are 2-ply 2x4's for added Strength.



Sliding Door Stay

Prevents door from closing on its own while open.

Sliding Door Jamblatch

7-inch hook and powerful cam-action pulls the door securely against the jamb. Eliminates rattling and wind damage. Opens inside only.



Sliding Door Bottom Guide

Door rolls easy. No binding or catching on the smooth, mated surfaces.

2x6 Center Match

2 Rows of Treated #1 Yellow Pine 2x6 Center Match Standard on Buildings.



Steel I-Beams

Engineered Steel I-Beams used for side door headers. Full clearance side door same height as end door.



Steel Walk Door

Various Options Available

- Solid Panel
- 22x22 Lite
- 22x36 9 Lite
- 22x36 Vent Lite
- Crossbucks
- Commercial Door
- Variety of Colors



Windows

- Horizontal Aluminum Single Pane Window Standard
- Thermo Window
- Vertical Single Hung
- Screen is Standard
- Optional Shutters
- Optional Internal Grills

Commercial Gutter

Unique Gutter goes on before roof steel. Designed to eliminate worry of snow & ice slide. Larger to carry more water.

Optional Thermax™ Insulation

Insulation and Condensation Control. Fire Rated Insulation.

Commercial Rake and Gutter

Buildings Standard with R.C. Rake and Gutter. More attractive than plain trim used by others. Gives the appearance of a 6" overhang.

Downspout

Same Color as Siding.

Trim Package

Trim available in all colors. Lengths up to 20' long eliminating splices.

Optional Overhang


Specially Designed Trim Package

Optional Boxed Overhang

Specially Designed Trim Package

Bird tight seal at end of building.

Steel Roofing and Siding



Advanced Product Design



Colored Screws Standard

Wheeling Corrugating Company's 29 Gauge Siding and Roofing Panels. Full-hard, high tensile, 100,000-plus psi steel holds up under heavy winds, snow loads, rain and work abuse. Premium, precision galvanizing adds uniform rust/corrosion protection. **40-year Warranty for Rust, 30-year for Fade-Chalk.** Wide assortment of durable colors ranging from bright contemporary colors to warm earth tones. All Wheeling Roofing and Siding is part of the Spectracote™ System, the most comprehensive, quality integrated manufacturing and paint finishing process in the industry.

American Made Steel



Finished Interior

Wheeling Corrugating Liner Panel with 6" R-19 Fiberglass Insulated Sides and 9" R-30 Fiberglass Insulated Ceiling Double Framed Wall



Limited Warranty

Lifetime Limited on Treated Timbers
 40 Years Rust
 30 Years Fade and Chalk
 40 Years Powder Coated Screws
 Life of Structure Snowload
 5 Years Roof Leak



Cupola

Variety of sizes. Colors to match your building. Variety of weathervanes. Attractive source for additional ventilation.

Optional Vented Closure Strips

For Continuous Ventilation.



Dutch Door

Variety of colors available to match building. Jamb is formed from a single sheet of steel (no seams) for added strength and appearance. Heavy Duty Hinges are Extra Strong and Bolt into Door Panel.



Sliding Door

Trim Colors to Match Building
Optional Crossbucks

Easy rolling track guaranteed for life of building.



C.H.I. Overhead Door

Variety of Sizes, Styles and Colors
Optional Windows
Optional Operators



Porch Options

Decorative Post Trim
Optional Wainscot
Mansard





Specialty Buildings



Built to Suit Your Needs!



66X168X18 and 80X88X18



42x72x14



24x110x9

66x80x16



66x112x16



70X360X16



72X96X16



72x104x12



36X32X8 and 40X64X14



A Sign of Quality
Material and
Workmanship Backed
by a Written Warranty.



42x88x12



36x56x10



36x50x12



42x64x14



30x40x9



36x64x12



42x64x12




36x56x12



36x56x12

For a Competitive Price Contact:



Since 1975

R.C. Buildings, Inc.

PO Box 286

Altamont, IL 62411

(618) 483-5204

To See More Pictures Go To
www.rcbuildings.com

American Made Products

